

# MENTOR II



The Cramaro Mentor II is a unique tarpaulin system combining the convenience of a cable system with the watertight effectiveness of a Side Roll system. With a 6" side drop, the Mentor II is ideal for ALL products whether a system is needed for dust containment or to keep the load dry.

#### Drive:

- The Mentor II has a shaft-less front header protecting the internal pulleys from salt, road grit, etc. The aluminum front assembly has a 9" (228mm) high wind deflector shield, which is ideal for high rise dog houses. The front assembly is watertight.
- The system is powered by a compact and Heavy Duty Superwinch 2.1 hp 12 or 24 volt motor with a 90:1 gear reducer. The Mentor II is only available as an electric model.
- The 4 gauge duplex wire and contact pads are used to reduce voltage drop resulting in extending the life of the motor.
- Wireless remote controls are available as an option.

#### Bows :

- Bows are assembled with 3 pieces: 2 bow ends and 1 steel arched bow. The bow ends are manufactured from a low friction polymer. The bows are spaced 30" (760 mm) apart, constructed from 1-1/8" (28mm) galvanized cold rolled steel tubing and are available in 6" (150mm) and 12" (300mm) arch heights.
- The three piece bow makes changing the center arched bow quick and easy. Now there is no need to replace the cable when changing the bow.
- The bow ends have a 6" (150mm) drop leg which the tarp attaches to. The cable goes through the top and bottom part of the leg. This combined with our unique "Anti-Lift System" dramatically reduces the system from lifting in windy conditions.

#### Tarpaulin:

- The tarpaulin is constructed from a premium heavy duty 22 oz (625 gm) vinyl (No seams in tarp, constructed from one piece of vinyl available in red, black and blue). It is secured to each bow with sealed attachment strips. Screws are **NOT** used to secure the tarp to the bows.
- First 8' of the tarp is triple reinforced with vinyl to prevent premature wearing. The entire length of the 6" drop side is double reinforced with vinyl.
- The 6" overhang meets state requirements to haul asphalt. The Mentor II comes standard with a long rear flap with buckles. Rear bow cap is available as an option. (Pictured above)

**Whether hauling sand and gravel, fertilizer or grain, the Mentor II system offers the versatility to meet ALL your needs.**

Protected by Pat.# 8,864,212  
and Patent Pending

